



## RPI M15A

High efficiency 3-phase solar inverters for the European market - Perfect choice for large-scale solar PV systems, such as those used in the commercial or agricultural sectors.

### Versatile applications

- Aluminium housing ensures long lasting protection against moisture and corrosion
- Wide input voltage range
- Suitable for indoor and outdoor applications (IP65)

### Maximum profitability

- Peak efficiency of 98.3 %
- 2 MPP trackers for increased flexibility and maximum yield
- Symmetrical and asymmetrical loading possible (33/67 % or 67/33 %)

# 15 kVA transformerless solar inverters

## Technical data RPI M15A

INPUT (DC)	RPI M15A
Max. recommended PV power	19 kW <sub>P</sub> <sup>1)</sup>
Max. input power	16.5 kW <sup>2)</sup>
Nominal power	15.6 kW
Voltage range	200 ... 1000 V
Startup voltage	250 V
MPP voltage range with full power	355 ... 820 V symmetrical load (50/50 %) With asymmetrical load: 475 ... 820 V (67 %) 235 ... 820 V (33 %)
Max. current	44 A (22 A per MPP tracker)
Max. number of MPP trackers	Parallel inputs: 1 MPP tracker Separate inputs: 2 MPP trackers
Input load	Symmetrical and asymmetrical (33/67 %)

OUTPUT (AC)	
Max. apparent power	15.75 kVA <sup>3) 4)</sup>
Nominal apparent power	15 kVA <sup>4)</sup>
Voltage range	230 ± 20% / 400 V ± 20 % <sup>5)</sup> 3 phase + PE or 3 phase + N + PE
Nominal current	22 A
Nominal frequency	50 / 60 Hz
Frequency range	50 / 60 Hz ± 5 Hz <sup>5)</sup>
Power factor adjustable	0.8 cap ... 0.8 ind
Total harmonic distortion (THD)	< 3 % @ nominal apparent power

### GENERAL SPECIFICATION


Model name	RPI-M15A
Part number Delta	RP1153FA0E0000
Max. efficiency	98.3 %
Efficiency EU	97.9 %
Operating temperature	-25 ... +60 °C
Full power without derating	-25 ... +40 °C
Storage temperature	-25 ... +60 °C
Humidity	0 ... 100 % non-condensing
Max. operating altitude	2000 m (above sea level)
Standard guarantee	5 years (guarantee extension is possible)

### MECHANICAL DESIGN

Size (L x W x D)	625 x 612 x 278 mm
Weight	43 kg
Cooling	Fans
AC connector	Amphenol C16-3 (included)
DC connector	4 pairs of Multi-Contact MC4 (included)
Communication interfaces	2 x RS485, 1 x Dry Contact, 1 x EPO
DC disconnecter	Integrated
Display	2 LEDs, 5 inch monochrome graphical LCD

SAFETY / STANDARDS	RPI M15A
Protection degree	IP65
Safety class	I
Configurable trip parameters	Yes
Insulation monitoring	Yes
Overload behavior	Current limitation; power limitation
Anti-islanding protection / Grid regulation	VDE-0126-1-1; VDE-AR-N 4105
EMC	EN61000-6-2; EN61000-6-3; EN61000-3-11; EN61000-3-12
Safety	IEC62109-1 / -2; CE compliance

- 1) When operated with balanced DC inputs (50/50 %)
- 2) Max. 11.1 kW per DC input with asymmetrical load
- 3) The maximum AC apparent power indicates the power an inverter is able to deliver. This maximum apparent power may not necessarily be reached.
- 4) Cos Phi = 1 (VA = W)
- 5) AC voltage and frequency range will be programmed according to the individual country requirements.



### United Kingdom

Email: [sales.uk@solar-inverter.com](mailto:sales.uk@solar-inverter.com)

Tel: 0800 051 4280 (Free Call)

### International

Email: [sales.europe@solar-inverter.com](mailto:sales.europe@solar-inverter.com)

Tel: +49 7641 455 547